
# K-PRAEZI DRUCKREGL OHNE EIGENLUF

Precision pressure regulators without air consumption

## Osobine

| | |
|---|---|
| **Ulazni pritisak** | Max. 16 bar |
| **Temperatura medija** | max. 80 °C |
| **Temperatura okoline** | Max. 80 °C |
| **Mediji** | Fine-filtered (5 µm), unlubricated compressed air, neutral gases |
| **Priključak manometra** | G 1/4 |
| **Zaptivni materijal** | NBR |
| **Kućište** | Die-cast zinc |
| **Ventilski konus** | FPM |






## Napomena

Ostali podaci na upit.

## Opis

Diaphragm pressure regulators with self-relieving design for applications requiring an accurate working pressure.

## Artikal

| Naziv | Navoj | Opseg regulacije | Protok (L/min) | A (mm) | B | C (mm) | D (mm) |
|---|---|---|---|---|---|---|---|
| **K- 07 25 09 39** | G 1/4 | 0 - 1 bar | 600 | 82,0 | 148,0 mm | 19,5 | 128,5 |
| **K- 07 25 09 40** | G 1/4 | 0.1 - 3 bar | 760 | 82,0 | 148,0 mm | 19,5 | 128,5 |
| **K- 07 25 09 41** | G 1/4 | 0.2 - 6 bar | 550 | 82,0 | 148,0 mm | 19,5 | 128,5 |
| **K- 07 25 09 42** | G 1/4 | 0.5 - 10 bar | 400 | 82,0 | 148,0 mm | 19,5 | 128,5 |

## Pribor

| | |
|---|---|
| **K-HALTERBAUSATZ STANDARD** | Holder |

*Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.*