

K-SVKM NW 5 SCHL UEM MS NI

Quick disconnect couplings DN 5, nickel-plated brass with hose connector, swivel nut and kink protector spring

HANSA FLEX

Osobine

Radni pritisak	0 - 35 bar, maximum static working pressure (non-pulsating)
Protok vazduha	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura medija	-20 °C to +100 °C
Kućište, čaura, telo ventila	Nickel-plated brass
Opruga, sigurnosni prsten, kugle	Stainless steel
Zaptivni materijal	NBR



Napomena

Ostali podaci na upit.

Opis

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

Artikal

Naziv	Priključak	Verzija	Dužina (mm)	SW (mm)
K- 07 35 06 67	Hose connection 6 x 4	Rigid	120,0	14
K- 07 35 06 68	Hose connection 8 x 6	Rigid	132,0	14
K- 07 35 06 69	Hose connection 6 x 4	Swivelling 360°	134,0	14
K- 07 35 06 70	Hose connection 8 x 6	Swivelling 360°	142,5	14