K-ENDPLATTEN V

End plate for HDM valve terminal

Osobine

Mediji	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
Radni pritisak	Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)
Upravljački pritisak	3 - 7 bar
Temperaturni opseg	-10 °C to +60 °C
Protok	200 Nl/min (Ø 4), 500 Nl/min (Ø 6), 800 Nl/min (Ø 8)
Broj upravljanja	Max. 16 (e.g. 16 spring return valves)
Funkcija	Blind (terminates the system)
Ručno pomoćno aktiviranje	Latching (bistable), Monostable (non-latching) version also available on request
Apsorbovanje snage	0.6 W per pilot
Vrsta zaštite	IP 65



Napomena

Ostali podaci na upit.

Opis

These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates.Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Dodatne informacije

Important: The scope of supply does not include a connector. Please order separately.

Artikal

Naziv	Funkcija
K- 07 15 22 50	Blind (terminates the system)