

K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continuous thread

HANSA **FLEX**

Osobine

Radni pritisak	Max. 50 bar
Priklučni navoj	acc. ISO 7-1
Materijal	black steel ST 37-2



Napomena

Ostali podaci na upit.

Opis

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Artikal

Naziv	Navoj	Dužina (mm)
K-07 40 35 30	R 1/4	25,0
K-07 40 35 33	R 3/8	26,0
K-07 40 35 29	R 1/2	34,0
K-07 40 35 32	R 3/4	36,0
K-07 40 35 26	R 1	43,0
K-07 40 35 28	R 1 1/4	48,0
K-07 40 35 27	R 1 1/2	48,0
K-07 40 35 31	R 2	56,0
K-07 40 50 36	R 2 1/2	65,0
K-07 40 50 37	R 3	71,0