

K-S-BKR M ENTL-BOHR ABSCHL

Safety ball valves, lockable, with relief port

HANSA FLEX

Osobine

| | |
|-----------------------|--|
| Radna temperatura | -10 °C to + 100 °C (depending on operating pressure) |
| Otvor za odzračivanje | M 5 (>1": Relief port G 1/4") |
| Opis navoja | Rp thread acc. to EN 10226 |
| Kućište | Nickel-plated brass |
| Ručna poluga | Steel - PVC coated |
| Kugla | hardchrome-plated brass |
| Zaptivka kugle | PTFE |
| Zaptivka vretena | PTFE |



Napomena

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)

Ostali podaci na upit.

Opis

2/2-way safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications. The valve shuts off the supply line and bleeds the application area. Lockable hand lever in closed position.

Dodatne informacije

The price does not include a padlock. Please order separately.

Artikal

| Naziv | DN | Navoj | PN (bar) | A (mm) | B (mm) | L (mm) |
|----------------|----|----------|----------|--------|--------|--------|
| K- 07 30 29 29 | 8 | Rp 1/4 | 14 | 96,0 | 49,0 | 45,0 |
| K- 07 30 29 30 | 10 | Rp 3/8 | 14 | 96,0 | 49,0 | 45,0 |
| K- 07 30 29 31 | 15 | Rp 1/2 | 14 | 96,0 | 51,0 | 59,0 |
| K- 07 30 29 32 | 20 | Rp 3/4 | 14 | 117,0 | 60,0 | 64,0 |
| K- 07 30 29 33 | 25 | Rp 1 | 14 | 117,0 | 64,0 | 81,0 |
| K- 07 30 29 34 | 32 | Rp 1 1/4 | 14 | 157,0 | 80,0 | 93,0 |
| K- 07 30 29 35 | 40 | Rp 1 1/2 | 14 | 157,0 | 86,0 | 102,0 |
| K- 07 30 29 36 | 50 | Rp 2 | 14 | 157,0 | 93,0 | 121,0 |

Pribor

K-VORHAENGESCHLOSS Padlock