


K-STECKVERSCHR IG SK MINI

Male connectors, female thread with outer hex, mini

HANSA FLEX

Osobine

| | |
|--------------------|--|
| Radni pritisak | Max. 10 bar, vacuum |
| Oblast primene | Air, vacuum |
| preporučena creva | PU or PA (nylon) |
| Mediji | Komprimovani vazduh |
| Norma | M thread acc. to DIN 13-1, with O-Ring |
| Temperaturni opseg | 0 °C to +60 °C |
| Zaptivna površina | O-ring (NBR) |
| Materijal | Plastic, Nickel plated brass |
| Pritisni prsten | Plastic |



Napomena

Ostali podaci na upit.

Opis

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

Artikal

| Naziv | Navoj | Ø mm za crevo spolja | L1 (mm) | SW |
|----------------|-------|----------------------|---------|------|
| K- 07 40 49 99 | M 3 | 3 mm | 16,7 | 8 mm |
| K- 07 40 50 00 | M 3 | 4 mm | 18,0 | 8 mm |
| K- 07 40 50 01 | M 5 | 3 mm | 16,2 | 8 mm |
| K- 07 40 50 02 | M 5 | 4 mm | 18,0 | 8 mm |