

# K-L-STECKVER L DREH MINI

Male elbows, long, swivel type, mini

**HANSA FLEX**

## Osobine

Radni pritisak	Max. 10 bar, vacuum
Oblast primene	Air, vacuum
preporučena creva	PU or PA (nylon)
Mediji	Komprimovani vazduh
Norma	M thread acc. to DIN 13-1, with O-Ring G thread acc. to DIN EN ISO 228-1, with O-Ring R thread acc. to ISO 7-1, thread coating
Temperaturni opseg	0 °C to +60 °C
Zaptivna površina	O-ring (NBR)
Materijal	Plastic, Nickel plated brass
Pritisni prsten	Plastic



## Napomena

Ostali podaci na upit.

## Opis

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

## Artikal

Naziv	Navoj	Ø mm za crevo spolja	L1 (mm)	L2 (mm)	SW
K- 07 40 23 53	M 3	3 mm	12,0	24,0	8 mm
K- 07 40 23 54	M 3	4 mm	14,0	29,2	8 mm
K- 07 40 23 55	M 5	3 mm	12,0	24,0	8 mm
K- 07 40 23 56	M 5	4 mm	14,0	29,2	8 mm
K- 07 40 23 57	M 5	6 mm	16,0	29,2	8 mm
K- 07 40 23 58	M 6	3 mm	12,0	24,5	10 mm
K- 07 40 23 59	M 6	4 mm	14,0	29,6	10 mm
K- 07 40 23 60	M 6	6 mm	16,0	29,6	10 mm
K- 07 40 23 61	G 1/8	4 mm	14,0	28,5	14 mm
K- 07 40 23 62	G 1/8	6 mm	16,0	28,5	14 mm
K- 07 40 23 63	R 1/8	4 mm	14,0	30,0	10 mm
K- 07 40 23 64	R 1/8	6 mm	16,0	30,0	10 mm