

K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

HANSA FLEX

Osobine

| | |
|--------------------|---|
| Radni pritisak | maks. 10 bara |
| Protok vazduha | 1.800 l/min (at 6 bar and $\Delta p = 1$ bar) |
| Temperatura medija | -20 °C to +150 °C |
| Kućište | Stainless steel 1.4404 |
| Navoj | Stainless steel 1.4404 |
| Unutrašnji delovi | Stainless steel 1.4404 |
| Dugme, ventila | Stainless steel 1.4404 |
| Zaptivni materijal | FKM |



Napomena

Not suitable for hitting / pulsating tools.

Ostali podaci na upit.

Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Dodatne informacije

Not suitable for hitting / pulsating tools.

Artikal

| Naziv | Priključak | Dužina (mm) | SW (mm) |
|----------------|--------------|----------------|------------|
| K- 07 35 12 79 | G 1/4 female | 71,5 | 21 |
| K- 07 35 12 80 | G 3/8 female | 75,5 | 21 |
| K- 07 35 12 81 | G 1/2 female | 77,5 | 24 |