


K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type

HANSA FLEX

Osobine

Radni pritisak	maks. 10 bara
Protok vazduha	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura medija	-20 °C to +150 °C
Kućište	Stainless steel 1.4404
Navoj	Stainless steel 1.4404
Unutrašnji delovi	Stainless steel 1.4404
Dugme, ventila	Stainless steel 1.4404
Zaptivni materijal	FKM



Napomena

Not suitable for hitting / pulsating tools.

Ostali podaci na upit.

Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

Dodatne informacije

Not suitable for hitting / pulsating tools.

Artikal

Naziv	Priključak	Dužina (mm)	SW (mm)
K- 07 35 12 76	G 1/4 male	70,5	21
K- 07 35 12 77	G 3/8 male	70,0	21
K- 07 35 12 78	G 1/2 male	72,5	25