

K-STECKVERSCHR IG SK

Male connectors, parallel female thread with outer hex

HANSA FLEX

Osobine

| | |
|-------------------|------------------|
| Radni pritisak | Max. 16 bar |
| Radna temperatura | -20 °C to +80 °C |
| Materijal | Mesing, niklovan |
| Pritisni prsten | Hostaform |
| Stezni prsten | Stainless steel |



Napomena

Ostali podaci na upit.

Opis

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

Artikal

| Naziv | Navoj | Ø mm za crevo spolja | L1 (mm) | SW |
|----------------|-------|----------------------|---------|-------|
| K- 07 40 25 06 | M 5 | 3 mm | 15,7 | 7 mm |
| K- 07 40 25 12 | G 1/8 | 4 mm | 26,2 | 10 mm |
| K- 07 40 25 13 | G 1/8 | 5 mm | 27,5 | 12 mm |
| K- 07 40 25 14 | G 1/8 | 6 mm | 27,1 | 12 mm |
| K- 07 40 25 15 | G 1/8 | 8 mm | 28,1 | 13 mm |
| K- 07 40 25 09 | G 1/4 | 4 mm | 28,6 | 10 mm |
| K- 07 40 47 15 | G 1/4 | 5 mm | 29,5 | 12 mm |
| K- 07 40 25 10 | G 1/4 | 6 mm | 29,3 | 12 mm |
| K- 07 40 25 11 | G 1/4 | 8 mm | 30,0 | 14 mm |
| K- 07 40 25 08 | G 1/4 | 10 mm | 31,8 | 16 mm |
| K- 07 40 25 16 | G 3/8 | 10 mm | 36,8 | 16 mm |
| K- 07 40 25 17 | G 3/8 | 12 mm | 37,0 | 19 mm |
| K- 07 40 25 07 | G 1/2 | 12 mm | 40,5 | 19 mm |