

K-DV GEW B SCHLITZ

Bidirectional flow control valves, air restriction at both ends (»B«), screw connection

HANSA FLEX

Osobine

| | |
|---|------------------------------------|
| Radni pritisak | maks. 10 bara |
| Temperaturni opseg | 0 °C to +70 °C |
| Šuplji zavrtnaj, obrtni rukavac, zavrtnaj za regulaciju | Nickel-plated brass |
| Unutrašnji delovi | Brass with a bare metal surface |
| Zaptivka O-prstena | NBR |
| Zaptivke (sa osiguračem) | Polyamide (glass fibre-reinforced) |



Napomena

Ostali podaci na upit.

Opis

For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. Compact type of construction, also ideal where space is restricted.

Artikal

| Naziv | Priključak | C (mm) | Navoj | SW | B (mm) |
|----------------|---------------------|--------|-------|-------|--------|
| K- 07 15 05 53 | M 5 female thread | 11,5 | M 5 | 8 mm | 24,5 |
| K- 07 15 05 58 | G 1/8 female thread | 16,0 | G 1/8 | 14 mm | 32,0 |
| K- 07 15 05 54 | G 1/4 female thread | 22,0 | G 1/4 | 17 mm | 40,0 |
| K- 07 15 25 26 | G 3/8 female thread | 26,0 | G 3/8 | 20 mm | 50,0 |
| K- 07 15 25 25 | G 1/2 female thread | 32,0 | G 1/2 | 26 mm | 61,0 |