

K-SOFT PVC SET SVKM TUE NW7,2

Soft PVC workshop hose kits with quick disconnect couplings and stems DN 7.2

HANSA FLEX

Osobine

Pogled iznutra Soft-PVC, black

Umetak pletenica od poliestra

spoljni izgled Soft-PVC, blue

Radna temperatura -20 °C to +60 °C



Napomena

Ostali podaci na upit.

Opis

Highly flexible hose for compressed air applications in workshop areas. Assembled with brass stem and brass quick disconnect coupling DN 7.2

Artikal

| Naziv | Ø creva unutra (mm) | Ø creva spolja (mm) | maks. radni pritisak pri 20°C (bar) | Dužina creva (m) |
|----------------|---------------------|---------------------|-------------------------------------|------------------|
| K- 07 10 11 91 | 6,3 | 11,0 | 15 | 5 |
| K- 07 10 11 85 | 6,3 | 11,0 | 15 | 10 |
| K- 07 10 11 87 | 6,3 | 11,0 | 15 | 15 |
| K- 07 10 11 88 | 6,3 | 11,0 | 15 | 20 |
| K- 07 10 11 90 | 6,3 | 11,0 | 15 | 25 |
| K- 07 10 11 99 | 9,0 | 14,5 | 15 | 5 |
| K- 07 10 11 93 | 9,0 | 14,5 | 15 | 10 |
| K- 07 10 11 95 | 9,0 | 14,5 | 15 | 15 |
| K- 07 10 11 96 | 9,0 | 14,5 | 15 | 20 |
| K- 07 10 11 98 | 9,0 | 14,5 | 15 | 25 |