


# K-T-STECK VERS DRE AG OR 1

Male branch tees, swivel type, parallel male thread with O-ring

**HANSA FLEX**

## Osobine

|                   |                  |
|-------------------|------------------|
| Radni pritisak    | Max. 16 bar      |
| Radna temperatura | -20 °C to +80 °C |
| Materijal         | Mesing, niklovan |
| Pritisni prsten   | Hostaform        |
| O-prsten          | NBR              |
| Stezni prsten     | Stainless steel  |



## Napomena

Ostali podaci na upit.

## Opis

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Artikal

| Naziv          | Navoj | Ø mm za crevo spolja | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|-------|----------------------|------------|------------|-------|
| K- 07 40 47 21 | M 5   | 4 mm                 | 37,2       | 15,3       | 9 mm  |
| K- 07 40 47 22 | M 5   | 6 mm                 | 43,8       | 15,3       | 9 mm  |
| K- 07 40 25 91 | G 1/8 | 4 mm                 | 37,2       | 19,1       | 12 mm |
| K- 07 40 25 92 | G 1/8 | 5 mm                 | 44,6       | 19,1       | 12 mm |
| K- 07 40 25 93 | G 1/8 | 6 mm                 | 43,8       | 19,1       | 12 mm |
| K- 07 40 25 94 | G 1/8 | 8 mm                 | 50,8       | 19,1       | 12 mm |
| K- 07 40 47 23 | G 1/4 | 4 mm                 | 37,2       | 21,1       | 14 mm |
| K- 07 40 25 89 | G 1/4 | 6 mm                 | 43,8       | 21,1       | 14 mm |
| K- 07 40 25 90 | G 1/4 | 8 mm                 | 50,8       | 21,1       | 14 mm |
| K- 07 40 25 88 | G 1/4 | 10 mm                | 54,4       | 21,8       | 14 mm |
| K- 07 40 25 97 | G 3/8 | 8 mm                 | 47,2       | 27,1       | 17 mm |
| K- 07 40 25 95 | G 3/8 | 10 mm                | 54,4       | 27,1       | 17 mm |
| K- 07 40 25 96 | G 3/8 | 12 mm                | 59,0       | 27,1       | 17 mm |
| K- 07 40 25 86 | G 1/2 | 12 mm                | 59,0       | 30,7       | 22 mm |
| K- 07 40 25 87 | G 1/2 | 14 mm                | 66,0       | 32,3       | 22 mm |