

K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media,
nonlinearity 0.2%

HANSA FLEX

Osobine

Tip	S-11
Napon	DC 10 (14) ... 30 V
Priključak na električnu mrežu	With right-angle connector acc. to DIN EN 175301-803 A
Vrsta zaštite	IP 65 acc. to EN 60529
Izlazni signal	4 to 20 mA, 2-wire
Nelinearnost	0.2% of span
Temperatura medija	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
Temperatura okoline	-20 °C to +80 °C
Delovi koji dodiruju merni materijal	CrNi steel 1.4571
Kućište	CrNi steel 1.4571



Opis

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Dodatne informacije

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Artikal

Naziv	Merni opseg	Navoj
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Rezervni delovi

K-ZUBEH DRUCKMESSUMFOR Accessoires for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%