

# K-T-STECK VERS DRE AG OR 2

Male branch tees, swivel type, parallel male thread with O-ring

**HANSA FLEX**

## Osobine

|                    |  |
|--------------------|--|
| Radni pritisak     | Max. 15 bar, coarse vacuum   |
| Oblast primene     | Air, vacuum  |
| preporučena creva  | PU or PA (nylon)   |
| Mediji             | Compressed air and all gases or liquids that are compatible with the materials |
| Temperaturni opseg | -20 °C to +80 °C   |
| Zapivna površina   | Parallel version: O-ring in housing  |
| Materijal          | Plastic, Nickel plated brass   |
| Pritisni prsten    | Plastic  |



## Napomena

Ostali podaci na upit.

## Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikal

| Naziv          | Navoj | Ø mm za crevo spolja | L1 (mm) | L2 (mm) | SW    |
|----------------|-------|----------------------|---------|---------|-------|
| K- 07 40 02 59 | M 5   | 4 mm                 | 36,0    | 21,1    | 8 mm  |
| K- 07 40 02 60 | M 5   | 6 mm                 | 40,0    | 22,2    | 8 mm  |
| K- 07 40 02 71 | G 1/8 | 4 mm                 | 36,0    | 19,0    | 14 mm |
| K- 07 40 02 72 | G 1/8 | 6 mm                 | 40,0    | 20,1    | 14 mm |
| K- 07 40 02 73 | G 1/8 | 8 mm                 | 45,4    | 25,7    | 14 mm |
| K- 07 40 02 68 | G 1/4 | 4 mm                 | 36,0    | 19,0    | 17 mm |
| K- 07 40 02 69 | G 1/4 | 6 mm                 | 40,0    | 20,1    | 17 mm |
| K- 07 40 02 70 | G 1/4 | 8 mm                 | 45,4    | 21,7    | 17 mm |
| K- 07 40 02 66 | G 1/4 | 10 mm                | 53,8    | 27,6    | 17 mm |
| K- 07 40 02 67 | G 1/4 | 12 mm                | 58,6    | 28,9    | 17 mm |
| K- 07 40 02 77 | G 3/8 | 6 mm                 | 40,0    | 21,2    | 20 mm |
| K- 07 40 02 78 | G 3/8 | 8 mm                 | 45,4    | 22,8    | 20 mm |
| K- 07 40 02 74 | G 3/8 | 10 mm                | 53,8    | 24,6    | 20 mm |
| K- 07 40 02 75 | G 3/8 | 12 mm                | 58,6    | 25,9    | 20 mm |
| K- 07 40 02 76 | G 3/8 | 16 mm                | 69,0    | 34,2    | 20 mm |
| K- 07 40 02 64 | G 1/2 | 6 mm                 | 40,0    | 23,6    | 24 mm |
| K- 07 40 02 65 | G 1/2 | 8 mm                 | 45,4    | 25,2    | 24 mm |
| K- 07 40 02 61 | G 1/2 | 10 mm                | 53,8    | 26,5    | 24 mm |
| K- 07 40 02 62 | G 1/2 | 12 mm                | 58,6    | 27,8    | 24 mm |
| K- 07 40 02 63 | G 1/2 | 16 mm                | 69,0    | 30,9    | 24 mm |