


# K-Y-STECK VERSCH DREH AG-K

Male branch Y-fittings, swivel type, conical male thread, coated

**HANSA FLEX**

## Osobine

Radni pritisak	Max. 15 bar, coarse vacuum
Oblast primene	Air, vacuum
preporučena creva	PU or PA (nylon)
Mediji	Compressed air and all gases or liquids that are compatible with the materials
Temperaturni opseg	-20 °C to +80 °C
Zapivna površina	Conical version: thread coating
Materijal	Plastic, Nickel plated brass
Pritisni prsten	Plastic



## Napomena

Ostali podaci na upit.

## Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## Artikal

Naziv	Navoj	Ø mm za crevo spolja	L1 (mm)	SW
K- 07 40 03 31	R 1/8	4 mm	42,0	10 mm
K- 07 40 03 32	R 1/8	6 mm	43,5	12 mm
K- 07 40 03 33	R 1/8	8 mm	46,8	14 mm
K- 07 40 03 29	R 1/8	10 mm	56,0	17 mm
K- 07 40 03 30	R 1/8	12 mm	59,8	21 mm
K- 07 40 03 26	R 1/4	4 mm	45,0	14 mm
K- 07 40 03 27	R 1/4	6 mm	46,0	14 mm
K- 07 40 03 28	R 1/4	8 mm	48,8	14 mm
K- 07 40 03 24	R 1/4	10 mm	58,0	17 mm
K- 07 40 03 25	R 1/4	12 mm	61,8	21 mm
K- 07 40 03 37	R 3/8	6 mm	47,5	17 mm
K- 07 40 03 38	R 3/8	8 mm	50,3	17 mm
K- 07 40 03 34	R 3/8	10 mm	59,0	17 mm
K- 07 40 03 35	R 3/8	12 mm	62,8	21 mm
K- 07 40 03 36	R 3/8	16 mm	72,0	24 mm
K- 07 40 03 22	R 1/2	6 mm	51,0	21 mm
K- 07 40 03 23	R 1/2	8 mm	53,8	21 mm
K- 07 40 03 19	R 1/2	10 mm	62,5	21 mm
K- 07 40 03 20	R 1/2	12 mm	65,8	21 mm
K- 07 40 03 21	R 1/2	16 mm	75,0	24 mm