

K-Y-STECK VB RED 10 BAR

Y unions, unequal (pressure max. 10 bar)

HANSA FLEX

Osobine

| | |
|--------------------|--|
| Radni pritisak | Max. 10 bar |
| Oblast primene | Air, vacuum |
| preporučena creva | PU or PA (nylon) |
| Mediji | Compressed air and all gases or liquids that are compatible with the materials |
| Temperaturni opseg | -20 °C to +80 °C |
| Materijal | Plastic, Nickel plated brass |
| Pritisni prsten | Plastic |



Napomena

Ostali podaci na upit.

Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artikal

| Naziv | Ø mm za crevo spolja | L1 (mm) |
|----------------|-----------------------|---------|
| K- 07 40 03 81 | 1 x 6 mm / 2 x 4 mm | 36,5 |
| K- 07 40 42 07 | 1 x 8 mm / 2 x 4 mm | 42,0 |
| K- 07 40 03 82 | 1 x 8 mm / 2 x 6 mm | 39,8 |
| K- 07 40 42 08 | 1 x 10 mm / 2 x 6 mm | 43,8 |
| K- 07 40 03 83 | 1 x 10 mm / 2 x 8 mm | 48,9 |
| K- 07 40 42 09 | 1 x 12 mm / 2 x 8 mm | 52,0 |
| K- 07 40 03 84 | 1 x 12 mm / 2 x 10 mm | 52,6 |