

K-L-STECKVER ISK DREH AG-K

Banjo elbows with inner hex, swivel type, conical male thread, coated

HANSA FLEX

Osobine

| | |
|--------------------|--|
| Radni pritisak | Max. 15 bar, coarse vacuum |
| Oblast primene | Air, vacuum |
| preporučena creva | PU or PA (nylon) |
| Mediji | Compressed air and all gases or liquids that are compatible with the materials |
| Temperaturni opseg | -20 °C to +80 °C |
| Zapivna površina | Conical version: thread coating |
| Materijal | Plastic, Nickel plated brass |
| Pritisni prsten | Plastic |



Napomena

Ostali podaci na upit.

Opis

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

Artikal

| Naziv | Navoj | Ø mm za crevo spolja | Imbus (mm) | L1 (mm) | L2 (mm) | SW |
|----------------|-------|----------------------|------------|---------|---------|-------|
| K- 07 40 05 10 | R 1/8 | 4 mm | 4,0 | 22,5 | 29,0 | 14 mm |
| K- 07 40 05 11 | R 1/8 | 6 mm | 4,0 | 21,5 | 29,0 | 14 mm |
| K- 07 40 05 12 | R 1/8 | 8 mm | 4,0 | 24,5 | 29,0 | 14 mm |
| K- 07 40 05 07 | R 1/4 | 4 mm | 4,0 | 24,5 | 38,0 | 17 mm |
| K- 07 40 05 08 | R 1/4 | 6 mm | 6,0 | 23,5 | 38,0 | 17 mm |
| K- 07 40 05 09 | R 1/4 | 8 mm | 6,0 | 26,5 | 38,0 | 17 mm |
| K- 07 40 05 05 | R 1/4 | 10 mm | 6,0 | 29,9 | 38,0 | 17 mm |
| K- 07 40 05 06 | R 1/4 | 12 mm | 6,0 | 30,8 | 38,0 | 17 mm |
| K- 07 40 05 15 | R 3/8 | 8 mm | 8,0 | 28,5 | 40,7 | 20 mm |
| K- 07 40 05 13 | R 3/8 | 10 mm | 8,0 | 31,9 | 40,7 | 20 mm |
| K- 07 40 05 14 | R 3/8 | 12 mm | 8,0 | 32,8 | 40,7 | 20 mm |
| K- 07 40 42 41 | R 1/2 | 10 mm | 8,0 | 34,7 | 45,2 | 24 mm |