

# K-T-STECK VB VA

Union tees

**HANSA FLEX**

## Osobine

|                            |                                                                 |
|----------------------------|-----------------------------------------------------------------|
| Pulsirajući radni pritisak | Max. 10 bar                                                     |
| Pritisak                   | Max. 15 bar (depending on pipe quality)                         |
| pogodan materijal cevi     | PVDF, PTFE, stainless steel, PA, PU                             |
| Temperatura okoline        | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| Materijal                  | Plemeniti čelik 1.4404                                          |
| Zaptivni materijal         | FKM                                                             |



## Napomena

Ostali podaci na upit.

## Opis

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

## Artikal

| Naziv          | Ø mm za crevo spolja | L1 (mm) | L2 (mm) |
|----------------|----------------------|---------|---------|
| K- 07 40 24 25 | 4 mm                 | 35,0    | 17,0    |
| K- 07 40 24 26 | 6 mm                 | 42,0    | 20,0    |
| K- 07 40 24 27 | 8 mm                 | 43,5    | 21,0    |
| K- 07 40 24 28 | 10 mm                | 50,0    | 25,0    |
| K- 07 40 24 29 | 12 mm                | 54,0    | 27,0    |