

# K-WERKST-SCHLAUCH SOFT

Workshop hose soft

**HANSA FLEX**

## Osobine

|                |                        |
|----------------|------------------------|
| Pogled iznutra | Soft-PVC, black        |
| Umetak         | pletenica od poliestra |
| spoljni izgled | Soft-PVC, blue         |
| Temperatura    | -20 °C to +60 °C       |
| Dužina rolne   | 50 m                   |



## Napomena

Ostali podaci na upit.

## Opis

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

## Artikal

| Naziv          | Ø creva unutra (mm) | Ø creva spolja (mm) | Max. working pressure resistance at 23°C (bar) | min. radijus savijanja (mm) |
|----------------|---------------------|---------------------|--|-----------------------------|
| K- 07 10 10 33 | 6,3                 | 11,0                | 15   | 23                          |
| K- 07 10 10 34 | 8,0                 | 13,0                | 15   | 28                          |
| K- 07 10 10 35 | 9,0                 | 14,5                | 15   | 32                          |
| K- 07 10 10 36 | 10,0                | 15,5                | 15   | 35                          |
| K- 07 10 10 37 | 12,7                | 19,0                | 15   | 45                          |
| K- 07 10 10 38 | 16,0                | 23,0                | 15   | 56                          |
| K- 07 10 10 39 | 19,0                | 26,5                | 15   | 67                          |
| K- 07 10 10 40 | 25,0                | 33,5                | 15   | 88                          |