

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Osobine

Pogled iznutra	Soft-PVC, black
Umetak	pletanica od poliestra
spoljni izgled	Soft-PVC, blue
Temperatura	-20 °C to +60 °C
Dužina rolne	50 m



Napomena

Ostali podaci na upit.

Opis

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Artikal

Naziv	Ø creva unutra (mm)	Ø creva spolja (mm)	Max. working pressure resistance at 23°C (bar)	min. radijus savijanja (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88