


K-W90 VERSCHR POLYPROPYLEN

Union elbows - polypropylene

HANSA FLEX

Osobine

| | |
|-------------------|---|
| Radni pritisak | Dependent on operating temperature; Max. 10 bar (at 20 °C); Max. 2.5 bar (at 90 °C) |
| Materijal | Polypropylene (PP) |
| Radna temperatura | Max. 90 °C |



Napomena

Ostali podaci na upit.

Opis

Chemically resistant to almost all inorganic acids and bases, even in high concentrations and at temperatures greater than 90 °C.

Artikal

| Naziv | za crevo | Navoj | L1 (mm) | L2 (mm) |
|----------------|--------------|-------|------------|------------|
| K- 07 40 41 79 | 4 mm / 6 mm | G 1/8 | 25,0 | 20,0 |
| K- 07 40 41 81 | 6 mm / 8 mm | G 1/8 | 30,0 | 23,0 |
| K- 07 40 41 83 | 8 mm / 10 mm | G 1/8 | 36,0 | 25,0 |
| K- 07 40 41 85 | 9 mm / 12 mm | G 1/8 | 40,0 | 27,0 |
| K- 07 40 41 86 | 4 mm / 6 mm | G 1/4 | 26,0 | 25,0 |
| K- 07 40 41 88 | 6 mm / 8 mm | G 1/4 | 30,0 | 27,0 |
| K- 07 40 41 90 | 8 mm / 10 mm | G 1/4 | 36,0 | 32,0 |
| K- 07 40 41 92 | 9 mm / 12 mm | G 1/4 | 40,0 | 31,0 |
| K- 07 40 41 93 | 4 mm / 6 mm | G 3/8 | 29,0 | 30,0 |
| K- 07 40 41 95 | 6 mm / 8 mm | G 3/8 | 33,0 | 27,0 |
| K- 07 40 41 97 | 8 mm / 10 mm | G 3/8 | 36,0 | 29,0 |
| K- 07 40 41 99 | 9 mm / 12 mm | G 3/8 | 40,0 | 31,0 |
| K- 07 40 42 00 | 4 mm / 6 mm | G 1/2 | 32,0 | 29,0 |
| K- 07 40 42 02 | 6 mm / 8 mm | G 1/2 | 36,0 | 29,0 |
| K- 07 40 42 04 | 8 mm / 10 mm | G 1/2 | 39,0 | 31,0 |
| K- 07 40 42 06 | 9 mm / 12 mm | G 1/2 | 43,0 | 33,0 |