


# K-T-STUECKE AG IG AG

Tees, male-female-male

**HANSA FLEX**

## Osobine

|                   |                              |
|-------------------|------------------------------|
| Radni pritisak    | 60 bar                       |
| Radna temperatura | Max. 150 °C                  |
| Unutrašnji navoj  | Parallel to DIN EN ISO 228-1 |
| Materijal         | Mesing, niklovan             |
| Spoljni navoj     | conical acc. DIN 2999        |



## Napomena

Ostali podaci na upit.

## Artikal

| Naziv          | Navoj   | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|---------|------------|------------|-------|
| K- 07 40 48 95 | G/R 1/8 | 37,0       | 21,0       | 10 mm |
| K- 07 40 48 96 | G/R 1/4 | 47,0       | 25,5       | 13 mm |
| K- 07 40 48 97 | G/R 3/8 | 52,0       | 28,0       | 17 mm |
| K- 07 40 48 98 | G/R 1/2 | 62,0       | 33,5       | 21 mm |
| K- 07 40 48 99 | G/R 3/4 | 66,5       | 36,5       | 25 mm |
| K- 07 40 49 00 | G/R 1   | 78,0       | 45,0       | 30 mm |