

# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

**HANSA FLEX**

## Osobine

|                   |  |
|-------------------|--|
| Primena           | Air, gases, oils, greases, fuels, organic and inorganic substances |
| Radna temperatura | -40 °C to +100 °C  |
| Vrsta priključka  | connection nipples and coupling NW 7,2                             |



## Napomena

Ostali podaci na upit.

## Opis

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## Artikal

| Naziv          | Ø creva unutra (mm) | Ø creva spolja (mm) | Ø spirale spolja (mm) | Namotaji | Max. working pressure resistance at 23°C (bar) | maks. radna dužina (m) |
|----------------|---------------------|---------------------|-----------------------|----------|--|------------------------|
| K- 07 10 12 95 | 6,3                 | 7,9                 | 75                    | 15       | 13   | 2,5                    |
| K- 07 10 12 96 | 6,3                 | 7,9                 | 75                    | 30       | 13   | 5,0                    |
| K- 07 10 12 97 | 6,3                 | 7,9                 | 75                    | 45       | 13   | 7,5                    |
| K- 07 10 12 65 | 7,9                 | 9,5                 | 115                   | 10       | 12   | 2,5                    |
| K- 07 10 12 66 | 7,9                 | 9,5                 | 115                   | 20       | 12   | 5,0                    |
| K- 07 10 12 67 | 7,9                 | 9,5                 | 115                   | 30       | 12   | 7,5                    |
| K- 07 10 12 68 | 9,5                 | 11,8                | 140                   | 8        | 11   | 2,5                    |
| K- 07 10 12 69 | 9,5                 | 11,8                | 140                   | 15       | 11   | 5,0                    |
| K- 07 10 12 70 | 9,5                 | 11,8                | 140                   | 23       | 11   | 7,5                    |

## Pribor

|                          |                                     |
|--------------------------|-------------------------------------|
| K-DREHBARE VERSCHR KNICK | Swivel adapters with kink protector |
| K-STARRE VERSCHRAUBUNG   | Rigid adapters with kink protector  |