K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass



Osobine	
Vrsta priključka	connection nipples and coupling NW 7,2
Radna temperatura	-40 °C to +74 °C



Napomena

Ostali podaci na upit.

Opis

.

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Artikal						
Naziv	Ø creva unutra (mm)	Ø creva spolja (mm)	Ø spoljnjeg navoja (mm)	Max. working pressure resistance at 23°C (bar)	maks. radna dužina	
<- 07 10 12 72	5,0	8,0	40	10	3,0	
K- 07 10 12 74	5,0	8,0	40	10	6,0	
<- 07 10 12 76	5,0	8,0	40	10	7,5	
K- 07 10 12 81	6,3	9,5	60	10	3,0	
(- 07 10 12 83	6,3	9,5	60	10	6,0	
(- 07 10 12 85	6,3	9,5	60	10	7,5	
C- 07 10 12 79	6,3	9,5	60	10	10,0	
(- 07 10 12 90	8,0	12,0	80	9	3,0	
<- 07 10 12 92	8,0	12,0	80	9	6,0	
(- 07 10 12 94	8,0	12,0	80	9	7,5	
C- 07 10 12 88	8,0	12,0	80	9	10,0	

Pribor	
K-DREHBARE VERSCHRAUBUNG	Swivel adapters