

K-ROHRLEIT ALU KALIBRIERT BLAU INFI

Pipe made of aluminium, calibrated, blue

HANSA FLEX

Osobine

Mediji	Compressed air, vacuum, inert gases
Koeficijent istezanja	0,024 mm/m °C
Radni pritisak	-0,99 bar - 15 bar
Temperaturni opseg	-20 °C to +80 °C
Boja	blue RAL 5010
Materijal	Aluminium UNI 9006/1 Al Mg 0,5 Si 0,4 Fe 0,2
Obrada površine	electrostatic coating



Napomene u vezi porudžbine

Special lengths on request

Artikal

Naziv	Spoljni-Ø (mm)	Debljina zida (mm)	Težina po metru (kg)	Specifična težina po dm3 (kg)	Dužina (m)	Jedinica pakovanja
K- 07 40 53 09	20	1,5	0,235	2,7	4,000	1 piece
K- 07 40 53 23	20	1,5	0,235	2,7	6,000	1 piece
K- 07 40 53 10	25	1,5	0,298	2,7	4,000	1 piece
K- 07 40 53 24	25	1,5	0,298	2,7	6,000	1 piece
K- 07 40 53 11	32	1,5	0,387	2,7	4,000	1 piece
K- 07 40 53 25	32	1,5	0,387	2,7	6,000	1 piece
K- 07 40 53 12	40	1,5	0,490	2,7	4,000	1 piece
K- 07 40 53 26	40	1,5	0,490	2,7	6,000	1 piece
K- 07 40 53 13	50	2,0	0,814	2,7	4,000	1 piece
K- 07 40 53 27	50	2,0	0,814	2,7	6,000	1 piece
K- 07 40 53 14	63	2,0	1,034	2,7	4,000	1 piece
K- 07 40 53 28	63	2,0	1,034	2,7	6,000	1 piece
K- 07 40 55 07	80	2,0	1,493	2,7	4,000	1 piece
K- 07 40 55 09	80	2,0	1,493	2,7	6,000	1 piece
K- 07 40 53 22	110	2,5	2,280	2,7	4,000	1 piece
K- 07 40 53 29	110	2,5	2,280	2,7	6,000	1 piece