

# K-VERTEILER 4-FACH HANSA PRO

Distributor 4-fold, HANSA PRO

**HANSA FLEX**

## Osobine

|                                 |  |
|---------------------------------|--|
| Temperatura medija              | -10 °C to +50 °C                             |
| Temperatura okoline             | -10 °C to +50 °C                             |
| Mediji                          | Komprimovani vazduh                          |
| Vrsta pričvršćivanje            | Line mounting, mounting kit or wall mounting |
| Položaj ugradnje                | Any  |
| Nominalni protok G 1/2          | 11.000 l/min (P1 = 6 bar/Delta P = 1 bar)    |
| Nominalni protok G 3/8          | 7.250 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| Nominalni protok pozadi (P - E) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| Nominalni protok gore (P - D)   | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| Nominalni protok dole (P - B)   | 5.500 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| Nominalni protok napred (P - C) | 2.250 l/min (P1 = 6 bar/Delta P = 1 bar)     |
| PE maks 11                      | 16 bar                                       |
| Kućište                         | PA66   |



## Artikal

| Naziv          | Priključak P + A | Priključak B | Priključak C | Priključak D | Priključak E | Konstrukciona veličina |
|----------------|------------------|--------------|--------------|--------------|--------------|------------------------|
| K- 07 25 22 46 | G 3/8 i          | G 1/2 i      | G 3/8 i      | G 1/4 i      | G 3/8 i      | 2                      |
| K- 07 25 22 47 | G 1/2 i          | G 1/2 i      | G 3/8 i      | G 1/4 i      | G 3/8 i      | 2                      |