

K-W90 STECK VB WAND 20-63 INFI

90°-elbow push-in connector Ø 20 mm – Ø 63 mm with wall mounting (adjustable)

HANSA FLEX

Osobine

Mediji	Compressed air, vacuum, inert gases
Radni pritisak	-0,99 bar - 15 bar
Temperaturni opseg	-20 °C to +80 °C
Zaptivka	NBR
Kučiče	Nickel-plated brass
Stezni prsten	Stainless steel 1.4301
Navrtka	Nickel-plated brass
O-prsten	NBR
Sigurnosni prsten	Technopolymer



Artikal

Naziv	Cev spolja Ø	Priključak	B (mm)	C (mm)	E (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L maks (mm)	L min (mm)	M (mm)	N (mm)	O (mm)	SW1 (mm)	SW2 (mm)
K- 07 40 54 11	20 mm	G 1/2"	31,5	19,5	34,5	35,0	51,0	35,0	40	22	64	50	20,0	21	30
K- 07 40 54 12	25 mm	G 3/4	38,5	23,0	42,5	37,0	62,0	39,0	40	22	64	50	20,0	26	35
K- 07 40 54 13	32 mm	G 1	46,0	28,0	52,0	41,0	74,5	48,5	40	26	64	50	20,0	34	45