K-DIGI DRUCKSCHA H DURCHF IA PF2A

Digital Flow Switch PF2Ax795

Osobine

Konstrukcija	Digital Flow Switch
maks. radni pritisak	0,1 MPa
maks. radni pritisak	1.50 MPa
Nominalni napon	24 V DC
Potrošnja struje	150 mA
Radni displej	3 digits, 7-Segment-LED lights at output signal = ON: OUT1: green, OUT2: red)
I/O kabl	without connection cable
Vrsta zaštite	IP 65
Temperatura medija	0 °C to +50 °C
Temperatura okoline	0 °C to +50 °C
Mediji	Air and nitrogen
Serija	PF2A
Ostali podaci	for High flow Integrated Display Type



Opis

Digital flow switch for high flow, series PF2A, for dry air, with integrated display unit, measuring range 30 to 3000 l/min, smallest adjustment unit 5 l/min, media temperature 0 to 50 °C, operating temperature range 0 to 50 °C, repetition accuracy max. ±3% of the measuring range, temperature characteristic max. ±2% of the measuring range. (0 to 50 °C, based on 25 °C), current consumption max. 150 mA, measuring principle thermistor (heating element), operating display 3-digit, 7-segment LED (illuminates at output signal ON OUT1: Green
OUT2: Red), operating pressure range 0.1 to 1.5 MPa, switch output PNP open collector 1 output and 1 analogue output (4 to 20 mA), with function to switch over the display unit, supply voltage 24 VDC, protection class IP 65, connection cable not included,connection size G 1 1/2

Artikal

Naziv	Priključni navoj	Jedinica podešavanja [Min] (L/min)	Merni opseg	Tačnost ponavljanja
K- 07 50 00 30	G 1	5,00	30 bis 3000 l/min	max. ±3 % from scale
K- 07 50 00 33	G 1 1/2	10,00	60 bis 6000 l/min	max. ±3 % from scale
K- 07 50 00 38	G 2	10,00	120 bis 12000 l/min	max. ±3 % from scale

Uprkos pažljivom proveravanju, ne možemo isključiti greške i ne preuzimamo nikakvu garanciju za navedene podatke.