

K-DIGIT DRUCKSCHA H 3DURCHF IA PF2A

Digital Flow Switch PF2A

HANSA FLEX

Osobine

Konstrukcija	Digital Flow Switch
maks. radni pritisak	0,1 MPa
Nominalni napon	24 V DC
Radni displej	3 digits, 7-Segment-LED lights at output signal = ON: OUT1: green, OUT2: red)
I/O kabl	without connection cable
Vrsta zaštite	IP 65
Temperatura medija	0 °C to +50 °C
Temperatura okoline	0 °C to +50 °C
Mediji	Air and nitrogen
Serija	PF2A
Ostali podaci	for High flow Integrated Display Type



Opis

Digital flow switch for high flow, series PF2A, for air and nitrogen, with integrated display unit, measuring range 150 to 3000 l/min, smallest adjustment unit 5 l/min, media temperature 0 to 50 °C, operating temperature range 0 to 50 °C, repetition accuracy max. $\pm 3\%$ of the measuring range, temperature characteristic max. $\pm 2\%$ of the measuring range. (0 to 50 °C, based on 25 °C), current consumption max. 150 mA, measuring principle thermistor (heating element), operating display 3-digit, 7-segment LED (illuminates at output signal ON OUT1: Green OUT2: Red), operating pressure range 0.1 to 1.5 MPa, switch output PNP open collector 1 output and 1 analogue output (1 to 5 V), with function to switch over the display unit, supply voltage 24 V DC, protection class IP 65, connection cable not included, connection size G 1 1/2

Artikal

Naziv	Priklučni navoj	Izlazni signal	Jedinica podešavanja [Min] (L/min)	Merni opseg	maks. radni pritisak (MPa)	Nominalni napon/ vrsta struje	Potrošnja struje max. (mA)	Tačnost ponavljanja
K-07 50 00 28	G 1	PNP + Analog output (1-5V)	5,00	150 bis 3000 l/min	1,50	24 VDC	150	max. $\pm 3\%$ from scale
K-07 50 00 29	G 1	PNP + Analog output (4-20mA)	5,00	150 bis 3000 l/min	1,50	-	150	max. $\pm 3\%$ from scale
K-07 50 00 31	G 1 1/2	PNP + Analog output (1-5V)	10,00	300 bis 6000 l/min	1,50	24 VDC	150	max. $\pm 3\%$ from scale
K-07 50 00 32	G 1 1/2	PNP + Analog output (4-20mA)	10,00	300 bis 6000 l/min	1,50	-	150	max. $\pm 3\%$ from scale
K-07 50 00 36	G 2	PNP + Analog output (1-5V)	10,00	600 bis 12000 l/min	1,50	24 VDC	150	max. $\pm 3\%$ from scale
K-07 50 00 37	G 2	PNP + Analog output (4-20mA)	10,00	600 bis 12000 l/min	1,50	-	150	max. $\pm 3\%$ from scale