

# K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

**HANSA FLEX**

## Osobine

|                      |   |
|----------------------|---|
| maks. radni pritisak | 0,7 MPa   |
| maks. radni pritisak | 0.10 MPa  |
| Verzija              | rack and pinion   |
| Temperatura medija   | 0 °C to +60 °C  |
| Temperatura okoline  | 0 °C to +60 °C  |
| Obrtni ugao          | 0 to 190°   |
| Mediji               | Komprimovani vazduh   |
| Seriya               | MSQ   |
| Ostali podaci        | narrow pivot table unit with low overall height<br>the rotation angle can be adjusted continuously<br>Positioning the housing allow for quick installation<br>the load can be mounted directly on the pivot<br>table<br>Air connections of 2 pages possible |



## Artikal

| Naziv          | Ø klipa (mm) | Pneumatski priključak | Konstruktivna veličina | Prigušivanje                            | Težina po metru (kg) |
|----------------|--------------|-----------------------|------------------------|---|----------------------|
| K- 07 55 01 13 | 6            | M 3                   | 1                      | without, with adjustment bolt           | 0,075                |
| K- 07 55 01 18 | 8            | M 5                   | 2                      | without, with adjustment bolt           | 0,105                |
| K- 07 55 01 21 | 10           | M 5                   | 3                      | elastic, with adjustment bolt           | 0,150                |
| K- 07 55 01 26 | 12           | M 5                   | 7                      | elastic, with adjustment bolt           | 0,250                |
| K- 07 55 01 11 | 15           | M 5                   | 10                     | elastic, with adjustment bolt           | 0,530                |
| K- 07 55 01 16 | 18           | M 5                   | 20                     | elastic, with adjustment bolt           | 0,990                |
| K- 07 55 01 19 | 21           | G 1/8                 | 30                     | elastic, with adjustment bolt           | 1,290                |
| K- 07 55 01 22 | 25           | G 1/8                 | 50                     | elastic, with adjustment bolt           | 2,080                |
| K- 07 55 01 24 | 28           | G 1/8                 | 70                     | elastic, with adjustment bolt           | 2,880                |
| K- 07 55 01 09 | 32           | G 1/8                 | 100                    | elastic, with adjustment bolt           | 4,090                |
| K- 07 55 01 14 | 40           | G 1/8                 | 200                    | elastic, with adjustment bolt           | 7,580                |
| K- 07 55 01 12 | 15           | M 5                   | 10                     | elastic, with integrated shock absorber | 0,540                |
| K- 07 55 01 17 | 18           | M 5                   | 20                     | elastic, with integrated shock absorber | 0,990                |
| K- 07 55 01 20 | 21           | G 1/8                 | 30                     | elastic, with integrated shock absorber | 1,290                |
| K- 07 55 01 23 | 25           | G 1/8                 | 50                     | elastic, with integrated shock absorber | 2,100                |
| K- 07 55 01 25 | 28           | G 1/8                 | 70                     | elastic, with integrated shock absorber | 2,880                |
| K- 07 55 01 10 | 32           | G 1/8                 | 100                    | elastic, with integrated shock absorber | 4,100                |
| K- 07 55 01 15 | 40           | G 1/8                 | 200                    | elastic, with integrated shock absorber | 7,650                |