

LKM IR ST DK

Naglavak sa utičnom spojnicom (vazduh) sa osiguračem

HANSA FLEX

Osobine

Konstrukcija	Naglavak brze spojnice
Priključak 1	BSP unutrašnji cilindrični navoj
Priključak 2	
Radni pritisak	maks. 12 bara
Protok vazduha	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Temperatura medija	-20 °C to +70 °C
Kućište	Aluminium, anodised
Navoj	Nickel-plated brass
Unutrašnji delovi	Stainless steel
Dugme, ventila	Hardened, galvanised steel
Zaptivni materijal	NBR



Napomena

Not suitable for hitting / pulsating tools.

Ostali podaci na upit.

Opis

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Artikal

Naziv	Priključni navoj	Priključak	Dužina (mm)	SW (mm)
LKM 06 IR ST DK	G 1/4" -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24