

Osobine

| | |
|-------------------------------|--|
| Oblast primene | Prehrambena industrija |
| Posebne karakteristike | Usisno i pritisno crevo pogodno za pivo i širok spektar prehrambenih sredstva koja ne sadrže masti Testirano da ne sadrži ftalate u skladu sa 1907/2006 / EG (REACH) čvrsto na vakuum 675 mmHg (26,6 inHg) |
| Dozvola | Ispunjava FDA 21 CFR 177.2600 BFR RECOMMENDATION XXI CAT 2 DM 21.03.73 E SEGUENTI EUROPEAN REGLEMENT 1935/2004/CE JAPAN-MINISTRY OF HEALTH AND WELFARE NOTICE NO.370,1959 AND NO.201,2006 3A Sanitarni standard klase II. RAL REGISTRATION G-74 |
| Pogled iznutra | specijalna EPDM bela guma, bez mirisa i otrova, opšte neškodljivo za namirnice |
| Umetak | sintetički tekstilni umetak, otporan na cepanje, i spirala od čelične žice |
| spoljni izgled | sintetička guma, veoma otporna na habanje, delovanje ozona i atmosferskih prilika |
| Boja | crvena |
| Temperatura min. | -40 °C |
| Temperatura max. | 120 °C |



Artikal

| Naziv | col | Unutrašnji-Ø (mm) | Spoljni-Ø (mm) | Debljina zida (mm) | Radni pritisak (bar) | Razorni pritisak (bar) | min. radijus savijanja (mm) |
|----------------|--------|-------------------|----------------|--------------------|----------------------|------------------------|-----------------------------|
| BRAU SD 13-6 | 1/2" | 13 | 24 | 5,5 | 16,0 | 48 | 45 |
| BRAU SD 16-6 | 5/8" | 16 | 27 | 5,5 | 16,0 | 48 | 55 |
| BRAU SD 19-6 | 3/4" | 19 | 31 | 6,0 | 16,0 | 48 | 65 |
| BRAU SD 25-6 | 1" | 25 | 37 | 6,0 | 16,0 | 48 | 90 |
| BRAU SD 32-6 | 1.1/4" | 32 | 44 | 6,0 | 16,0 | 48 | 120 |
| BRAU SD 38-6.5 | 1.1/2" | 38 | 53 | 6,5 | 16,0 | 48 | 155 |
| BRAU SD 50-8 | 2" | 50 | 66 | 8,0 | 16,0 | 48 | 215 |
| BRAU SD 63-8 | 2.1/2" | 63 | 81 | 8,0 | 16,0 | 48 | 275 |
| BRAU SD 75-9 | 3" | 75 | 94 | 9,5 | 16,0 | 48 | 330 |
| BRAU SD 100-10 | 4" | 100 | 120 | 10,0 | 16,0 | 48 | 450 |

BD = radni pritisak – DN = nominalni prečnik, nominalna širina