

## Osobine

<b>Oblast primene</b>	Prehrambena industrija
<b>Posebne karakteristike</b>	Usisno i pritisno crevo pogodno za pivo i širok spektar prehrambenih sredstva koja ne sadrže masti Testirano da ne sadrži ftalate u skladu sa 1907/2006 / EG (REACH) čvrsto na vakuum 675 mmHg (26,6 inHg)
<b>Dozvola</b>	Ispunjava FDA 21 CFR 177.2600 BFR RECOMMENDATION XXI CAT 2 DM 21.03.73 E SEGUENTI EUROPEAN REGLEMENT 1935/2004/CE JAPAN-MINISTRY OF HEALTH AND WELFARE NOTICE NO.370,1959 AND NO.201,2006 3A Sanitarni standard klase II. RAL REGISTRATION G-74
<b>Pogled iznutra</b>	specijalna EPDM bela guma, bez mirisa i otrova, opšte neškodljivo za namirnice
<b>Umetak</b>	sintetički tekstilni umetak, otporan na cepanje, i spirala od čelične žice
<b>spoljni izgled</b>	sintetička guma, veoma otporna na habanje, delovanje ozona i atmosferskih prilika
<b>Boja</b>	crvena
<b>Temperatura min.</b>	-40 °C
<b>Temperatura max.</b>	120 °C



## Artikal

Naziv	col	Unutrašnji-Ø (mm)	Spoljni-Ø (mm)	Debljina zida (mm)	Radni pritisak (bar)	Razorni pritisak (bar)	min. radijus savijanja (mm)
BRAU SD 13-6	1/2"	13	24	5,5	16,0	48	45
BRAU SD 16-6	5/8"	16	27	5,5	16,0	48	55
BRAU SD 19-6	3/4"	19	31	6,0	16,0	48	65
BRAU SD 25-6	1"	25	37	6,0	16,0	48	90
BRAU SD 32-6	1.1/4"	32	44	6,0	16,0	48	120
BRAU SD 38-6.5	1.1/2"	38	53	6,5	16,0	48	155
BRAU SD 50-8	2"	50	66	8,0	16,0	48	215
BRAU SD 63-8	2.1/2"	63	81	8,0	16,0	48	275
BRAU SD 75-9	3"	75	94	9,5	16,0	48	330
BRAU SD 100-10	4"	100	120	10,0	16,0	48	450

BD = radni pritisak – DN = nominalni prečnik, nominalna širina