


## Osobine

Priključak	Priključci za ulje pozadi: A + B = G 3/8"; ulje koje curi = G 1/8"
Verzija	Economy variant Zaptivke NBR Osovina Ø 16mm
Ulazni i povratni pritisak sa prelivnim vodom max.	140 bar



## Artikal

Naziv	Protok max. (L/min)	Usisni volumen (cc)	Broj obrtaja min. (rpm)	Broj obrtaja max. (rpm)	Obrtni momenat max. (N-m)	Opadanje pritiska max. (bar)	Pmax. at 0-100 rpm (bar)	Pmax. at 100-300 rpm (bar)	Pmax. at 300-600 rpm (bar)	Pmax. at 600 rpm (bar)	L (mm)	Težina (kg)
HK HM BMM 008	16	8,2	50	1950	11	100	140	90	30	15	105	1,9
HK HM BMM 012	20	12,9	40	1550	16	100	140	90	30	15	107	2,0
HK HM BMM 020	20	19,9	30	1000	25	100	140	90	30	15	110	2,1
HK HM BMM 032	20	31,8	30	630	40	100	140	90	30	-	115	2,2
HK HM BMM 040	20	39,8	25	500	45	90	140	90	30	-	118	2,3
HK HM BMM 050	20	50,3	20	400	46	70	140	90	-	-	123	2,4

max. pressure on shaft seal (without leak oil line) or pressure in leak oil line – Vrednosti za obrtni momenat i opadanje pritiska važe za stalni režim rada

## Pribor

HK EPMM F Prirubnica za Gerotor motore