

# HK B3/B14 230/400V IE3

Elektromotor B3/B14 230/400V IE2

**HANSA FLEX**

## Osobine

<b>Verzija</b>	Konstrukcija B3/B14 sa stopalima koja se mogu skinuti
<b>Vrsta zaštite</b>	IP 55
<b>Temperatura okoline</b>	-20 °C do +40 °C
<b>Materijal</b>	Kućište: Aluminijum lakirano



## Opis

Motori sa kratkospojnim rotorom i sopstvenim hlađenjem koji štede energiju  
Visoka efikasnost IE3 - IEC60034-30:2009  
Dimenzionisani napon 230/400V 50Hz, 460V 60Hz; 4-polno  
Tolerancija napona +/- 5%

## Artikal

Naziv	n 50 Hz (rpm)	P 50 Hz (kW)	I 50 Hz (A)	LF 50 Hz	H (mm)	A (mm)	B (mm)	C (mm)	Ø D osovina (mm)	Ø E (mm)	Ø F (mm)	η (IE3) %	Težina (kg)
HKK 405A 80B4 IE3	1420	0,75	1,80	0,74	80	125	255	209	19	80	120	82,5	13,0
HKK 406A 90SA4 IE3	1445	1,10	2,60	0,74	90	140	280	230	24	95	140	84,1	17,0
HKK 407A 90LB4 IE3	1445	1,50	3,40	0,74	90	140	305	230	24	95	140	85,3	20,0
HKK 408A 100LA4 IE3	1435	2,20	4,70	0,78	100	160	343	256	28	110	160	86,7	27,0
HKK 409A 100LB4 IE3	1435	3,00	6,30	0,78	100	160	343	256	28	110	160	87,7	31,5

P 50 Hz = nominal output at 400 V/50 Hz – n 50 Hz = nominalni broj obrtaja pri 400 V/50 Hz – I 50 Hz = nominalna struja pri 400 V/50 Hz – LF 50 Hz = koeficijent snage cos phi pri 50 Hz – η (IE3) = efficiency to IE3 in % (at full load)