

PRT RED M S

Perrot Kaplini Azaltması Diři Ucu, Erkek Ucunun Üstünde

HANSA FLEX

Özellikler

| | |
|----------------------|-------------------|
| Baęlantı 1 | Kavrama diři ucu |
| Sızdırmazlık řekli 1 | O-Ring contalı |
| Baęlantı 2 | Kavrama erkek ucu |
| Yüzey koruması | ateřle galvanize |



Ürün

| Tanım | Çalıřma basıncı (bar) | Kavrama ölçüsü (mm) |
|-------------------|--------------------------|------------------------|
| PRT RED M70-S50 | 12,0 | 70,0 / 50,0 |
| PRT RED M89-S70 | 12,0 | 89,0 / 70,0 |
| PRT RED M108-S70 | 12,0 | 108,0 / 70,0 |
| PRT RED M108-S89 | 12,0 | 108,0 / 89,0 |
| PRT RED M133-S89 | 12,0 | 133,0 / 89,0 |
| PRT RED M133-S108 | 12,0 | 133,0 / 108,0 |
| PRT RED M159-S108 | 12,0 | 159,0 / 108,0 |
| PRT RED M159-S133 | 12,0 | 159,0 / 133,0 |
| PRT RED M216-S159 | 12,0 | 216,0 / 159,0 |