

PRT S HR

Perrot Kaplini Erkek Ucu Dış Mil

HANSA FLEX

Özellikler

| | |
|----------------|------------------------|
| Bağlantı 1 | Kavrama erkek ucu |
| Bağlantı 2 | BSP dış dış silindirik |
| Malzeme | Çelik |
| Yüzey koruması | ateşle galvanize |



Ürün

| Tanım | Çalışma basıncı (bar) | Kavrama ölçüsü (mm) | G1 |
|--------------------|-----------------------|---------------------|--------------|
| PRT S 50 HR 1.1/2 | 25,0 | 50,0 | G 1.1/2" -11 |
| PRT S 50 HR 2 | 25,0 | 50,0 | G 2" -11 |
| PRT S 70 HR 2 | 25,0 | 70,0 | G 2" -11 |
| PRT S 70 HR 2.1/2 | 25,0 | 70,0 | G 2.1/2" -11 |
| PRT S 70 HR 3 | 25,0 | 70,0 | G 3" -11 |
| PRT S 89 HR 2.1/2 | 25,0 | 89,0 | G 2.1/2" -11 |
| PRT S 89 HR 3 | 25,0 | 89,0 | G 3" -11 |
| PRT S 108 HR 2.1/2 | 25,0 | 108,0 | G 2.1/2" -11 |
| PRT S 108 HR 3 | 25,0 | 108,0 | G 3" -11 |
| PRT S 108 HR 4 | 25,0 | 108,0 | G 4" -11 |
| PRT S 133 HR 2.1/2 | 25,0 | 133,0 | G 2.1/2" -11 |
| PRT S 133 HR 4 | 25,0 | 133,0 | G 4" -11 |
| PRT S 133 HR 5 | 25,0 | 133,0 | G 5" -11 |
| PRT S 159 HR 2.1/2 | 25,0 | 159,0 | G 2.1/2" -11 |
| PRT S 159 HR 4 | 25,0 | 159,0 | G 4" -11 |
| PRT S 159 HR 6 | 25,0 | 159,0 | G 6" -11 |