

K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA FLEX

Özellikler

Bağlantı 1 + 2	metrik dış dış, silindirik
Standart	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Ruhsat	German Technical Surveyance Association (TÜV)-type approved (Certificate R 9910199)
Sıcaklık min.	-40 °C
Sıcaklık max.	90 °C
Malzeme	PUR



Ek bilgiler

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Ürün

Tanım	G1 + G2	İç çap (mm)	Dış çap (mm)	Et Kalınlığı (mm)	Uzunluk (m)	Renk
K- 07 10 13 21	M 16 x 1,5	8,0	12,0	2,0	4,50	siyah
K- 07 10 13 22	M 16 x 1,5	8,0	12,0	2,0	4,50	sarı
K- 07 10 13 23	M 16 x 1,5	8,0	12,0	2,0	4,50	kırmızı
K- 07 10 13 24	M 16 x 1,5	8,0	12,0	2,0	5,50	siyah
K- 07 10 13 25	M 16 x 1,5	8,0	12,0	2,0	5,50	sarı
K- 07 10 13 26	M 16 x 1,5	8,0	12,0	2,0	5,50	kırmızı