K-DIFFERENZDRUCKMANO Z

Differential pressure gauges with parallel male connector

Özellikler

Tip	711.12
Model	Bourdon-tube pressure gauge with parallel male connector and two separate measuring systems
Uygulama	to measure differential pressures or two different pressures For gaseous or liquid media which do not corrode copper alloy,do not have high viscosity and do not crystallise
Kalite sınıfı	1,6
Akışkan sıcaklığı	maks. +60 °C
Ortam sıcaklığı	-20 °C ile +60 °C arasında
Mahfaza, halka	Steel, black
Ölçme parçası ve gösterge mekanizması malzemesi	Bakır alaşım
Kontrol camı	Flat instrument glass



Açıklama

Diğer bilgiler, istek üzerinedir.

Ürün

Tanım	Ölçme alanı	Ø (mm)	Bağlantı
K- 07 20 00 55	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 00 56	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 00 57	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 00 58	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 00 59	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 60	0 - 10.0 bar	100,0	G 1/2"

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.