K-MANO 1

Pressure gauges (CrNi steel type / safety housing)

Özellikler

Tip	232.30
Model	Bourdon-tube pressure gauge, CrNi steel type, with solid baffle wall and blow-out (safety housing)
Uygulama	For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere
Kalite sınıfı	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Akışkan sıcaklığı	max. +200 °C
Ortam sıcaklığı	-40 °C to +60 °C
Gövde	CrNi steel
Kontrol camı	Laminated safety glass Ø 63 = Polycarbonate



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Safety version with more fracture-resistant separating wall

Ürün

Tanım	Ölçme alanı	Ø (mm)	Bağlantı
K- 07 20 07 15	-1 / 0.0 bar	63,0	G 1/4 "
K- 07 20 07 16	0 - 1.6 bar	63,0	G 1/4 "
K- 07 20 07 17	0 - 2.5 bar	63,0	G 1/4 "
K- 07 20 07 18	0 - 4.0 bar	63,0	G 1/4 "
K- 07 20 07 19	0 - 6.0 bar	63,0	G 1/4 "
K- 07 20 07 20	0 - 10.0 bar	63,0	G 1/4 "
K- 07 20 07 21	0 - 16.0 bar	63,0	G 1/4 "
K- 07 20 07 22	0 - 25.0 bar	63,0	G 1/4 "
K- 07 20 07 23	0 - 40.0 bar	63,0	G 1/4 "
K- 07 20 07 24	0 - 60.0 bar	63,0	G 1/4 "
K- 07 20 07 25	0 - 100.0 bar	63,0	G 1/4 "
K- 07 20 01 97	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 01 98	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 01 99	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 02 00	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 02 01	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 02 02	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 02 03	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 02 04	0 - 25.0 bar	100,0	G 1/2"
K- 07 20 02 05	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 02 06	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 02 07	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 02 08	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 02 09	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 02 10	0 - 400.0 bar	100,0	G 1/2"

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.