

# K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

**HANSA FLEX**

## Özellikler

Tip	422.12 (robust), 432.50 (chemical)
Model	Diaphragm pressure gauge in robust design or for chemical applications
Uygulama	at chemical applications in aggressive environments for gaseous or liquid media,
Kalite sınıfı	1,6
Akışkan sıcaklığı	max. +100 °C
Ortam sıcaklığı	-20 °C ile +60 °C arasında
Ø ölçme flanşı	100 mm
Mahfaza, halka	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
Ölçme birimi	CrNi steel
Kontrol camı	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
Gösterge mekanizması	Copper alloy (robust type), CrNi steel (type for chemical applications)



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Ürün

Tanım	Ölçme alanı	Ø (mm)	Bağlantı
K- 07 20 10 99	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 00	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 11 01	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 11 02	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 11 03	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 11 04	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 11 05	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 11 06	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 11 07	0 - 25.0 bar	100,0	G 1/2"