

K-PRMM ROB U

Robust diaphragm pressure gauges, connection radial on bottom

HANSA FLEX

Özellikler

| | |
|----------------------|---|
| Tip | 422.12 (robust), 432.50 (chemical) |
| Model | Diaphragm pressure gauge in robust design or for chemical applications |
| Uygulama | at chemical applications in aggressive environments for gaseous or liquid media, |
| Kalite sınıfı | 1,6 |
| Akışkan sıcaklığı | max. +100 °C |
| Ortam sıcaklığı | -20 °C ile +60 °C arasında |
| Ø ölçme flanşı | 100 mm |
| Mahfaza, halka | Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications) |
| Ölçme birimi | CrNi steel |
| Kontrol camı | Flat instrument glass (robust type), Laminated safety glass (type for chemical applications) |
| Gösterge mekanizması | Copper alloy (robust type), CrNi steel (type for chemical applications) |



Açıklama

Diğer bilgiler, istek üzerinedir.

Ürün

| Tanım | Ölçme alanı | Ø (mm) | Bağlantı |
|----------------|---------------|--------|----------|
| K- 07 20 10 99 | -1 / +1.5 bar | 100,0 | G 1/2" |
| K- 07 20 11 00 | 0 - 1.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 01 | 0 - 1.6 bar | 100,0 | G 1/2" |
| K- 07 20 11 02 | 0 - 2.5 bar | 100,0 | G 1/2" |
| K- 07 20 11 03 | 0 - 4.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 04 | 0 - 6.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 05 | 0 - 10.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 06 | 0 - 16.0 bar | 100,0 | G 1/2" |
| K- 07 20 11 07 | 0 - 25.0 bar | 100,0 | G 1/2" |