

# K-PRMM CHEMIE U

Diaphragm pressure gauges for chemical applications, connection radial on bottom

**HANSA FLEX**

## Özellikler

<b>Tip</b>	422.12 (robust), 432.50 (chemical)
<b>Model</b>	Diaphragm pressure gauge in robust design or for chemical applications
<b>Uygulama</b>	at chemical applications in aggressive environments for gaseous or liquid media,
<b>Kalite sınıfı</b>	1,6
<b>Akışkan sıcaklığı</b>	max. +100 °C
<b>Ortam sıcaklığı</b>	-20 °C ile +60 °C arasında
<b>Ø ölçme flanşı</b>	100 mm
<b>Mahfaza, halka</b>	Grey cast iron / CrNi steel, black (robust type), CrNi steel (type for chemical applications)
<b>Ölçme birimi</b>	CrNi steel
<b>Kontrol camı</b>	Flat instrument glass (robust type), Laminated safety glass (type for chemical applications)
<b>Gösterge mekanizması</b>	Copper alloy (robust type), CrNi steel (type for chemical applications)



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Ürün

Tanım	Ölçme alanı	Ø (mm)	Bağlantı
K- 07 20 10 25	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 10 26	0 - 10.0 bar	100,0	G 1/2"