


K-MANO ABSPH MUF MUF

Pressure gauge stopcocks, female - female

Özellikler

Uygulama	For all pressure gauges with a flat gasket acc. to DIN 16258
Bařınç aralıęı	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
Sıcaklık	Max. +50 °C
Gövde	Brass with a bare metal surface or stainless steel 1.4571
Tutma kolu	Plastic
Kontrol flanřı	-



Açıklama

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Dięer bilgiler, istek üzerinedir.

Açıklama

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Ek bilgiler

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Ürün

Tanım	Mil	PN (bar)	SW (mm)	Malzeme
K- 07 20 10 88	G 1/4	6	17	Pirinç
K- 07 20 10 89	G 3/8	16	22	Pirinç
K- 07 20 10 91	G 1/2	25	27	Pirinç
K- 07 20 10 90	G 1/2	25	27	Stainless steel
K- 07 20 10 93	G 1/2	25	27	Pirinç
K- 07 20 10 92	G 1/2	25	27	Pirinç