

K-SPIR SCHL

Spiral hose, without fittings

HANSA FLEX

Özellikler

Uygulama	Air, gases, oils, greases, fuels, organic and inorganic substances
İşletim ısısı	-40 °C to +100 °C



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

Ürün

Tanım	Ø hortum iç (mm)	Ø hortum dış (mm)	Ø spiral dış (mm)	Sargılar	Max. working pressure resistance at 23°C (bar)	maks. çalışma uzunluğu (m)
K- 07 10 07 51	3,1	4,7	38	144	22	10,0
K- 07 10 07 52	4,8	6,3	75	140	16	22,5
K- 07 10 07 53	6,3	7,9	75	135	13	22,5
K- 07 10 07 49	7,9	9,5	115	90	12	22,5
K- 07 10 07 50	9,5	11,8	140	70	11	22,5

Aksesuar

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector