

K-SPIR SCHL DREH VERSCHRAU V

Spiral hose, with swivel adapter and kink protector, braided

HANSA FLEX

Özellikler

Bağlantı tipi with kink protector, swivel type

İşletim ısısı -40 °C to +74 °C



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Ürün

Tanım	Mil	Ø hortum iç (mm)	Ø hortum dış (mm)	Ø dış sargı (mm)	Max. working pressure resistance at 23°C (bar)	maks. çalışma uzunluğu (m)
K- 07 10 07 43	G 1/4	6,3	9,5	42	14	3,0
K- 07 10 07 44	G 1/4	6,3	9,5	42	14	6,0
K- 07 10 07 45	G 1/4	6,3	9,5	42	14	7,5
K- 07 10 07 46	G 3/8	8,0	12,0	55	14	3,0
K- 07 10 07 47	G 3/8	8,0	12,0	55	14	6,0
K- 07 10 07 48	G 3/8	8,0	12,0	55	14	7,5

Aksesuar

K-DREHBARE VERSCHRAUBUNG Swivel adapters