

K-VSEH AIRKRAFT

Receptacle combinations »airkraft«

HANSA FLEX

Özellikler

Gövde	Amaplast with hinged cover
Mahfazada entegre	Hanging eyelets, wall mounting fixing and standing feet
Sigorta	Beneath transparent lid (4 MW)
Model	Pre-wired
Hat girişleri (iletimleri)	Top: 1 x M 32, 1 x M 25, 2 x M 20; Side: 1 x M 25; One opening at the top for pneumatic connection(all openings can be cut out)
Koruma sınıfı	IP 44



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Receptacle combination with low power, high power or combined connections. Equipped with a pneumatic connection (DN 7.2 coupling with 9 mm stem).

Ürün

Tanım	Donanım	Renk
K- 07 10 03 52	4 Schuko socket 16 A 2p + E 230 V	sarı
K- 07 10 03 51	3 Schuko socket 16 A 2p + E 230 V, 1 CEEform socket 16 A 5p 400 V	gümüş

Aksesuar

K-VT 2 KUPPL 7,2 STECKNIP MS	Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8
K-ZUBEH VSEH 3 KRAFT AIRKRAFT	Accessories for receptacle combinations »3-Kraft« and »airkraft«