


K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

HANSA FLEX

Özellikler

Çalışma basıncı	0 - 35 bar, maximum static working pressure (non-pulsating)
Akış hava	560 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Akışkan sıcaklığı	-20 °C to +100 °C
Kilidi açma kovanı	Anodised aluminium
Yay, patlama halkası, bilyeler	stain less steel
Yalıtım malzemesi	NBR



Açıklama

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. Diğer bilgiler, istek üzerinedir.

Açıklama

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Ürün

Tanım	Bağlantı	Renk	Uzunluk (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	yeşil	45,0	14
K- 07 35 06 81	G 1/4 male	yeşil	47,0	17
K- 07 35 06 82	G 1/8 female	yeşil	45,0	14
K- 07 35 06 83	G 1/4 female	yeşil	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	mavi	45,0	14
K- 07 35 06 89	G 1/4 male	mavi	47,0	17
K- 07 35 06 90	G 1/8 female	mavi	45,0	14
K- 07 35 06 91	G 1/4 female	mavi	47,0	17
K- 07 35 06 92	G 1/8 male	kırmızı	45,0	14
K- 07 35 06 93	G 1/4 male	kırmızı	47,0	17
K- 07 35 06 94	G 1/8 female	kırmızı	45,0	14
K- 07 35 06 95	G 1/4 female	kırmızı	47,0	17