


# K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

**HANSA FLEX**

## Özellikler

|                                |   |
|--------------------------------|---|
| Çalışma basıncı                | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Akış hava                      | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| Akışkan sıcaklığı              | -20 °C to +100 °C   |
| Kilidi açma kovanı             | Anodised aluminium  |
| Yay, patlama halkası, bilyeler | stain less steel  |
| Yalıtım malzemesi              | NBR   |



## Açıklama

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings. Diğer bilgiler, istek üzerinedir.

## Açıklama

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

## Ürün

| Tanım          | Bağlantı     | Renk    | Uzunluk (mm) | SW (mm) |
|----------------|--------------|---------|--------------|---------|
| K- 07 35 06 80 | G 1/8 male   | yeşil   | 45,0         | 14      |
| K- 07 35 06 81 | G 1/4 male   | yeşil   | 47,0         | 17      |
| K- 07 35 06 82 | G 1/8 female | yeşil   | 45,0         | 14      |
| K- 07 35 06 83 | G 1/4 female | yeşil   | 47,0         | 17      |
| K- 07 35 06 84 | G 1/8 male   | Brown   | 45,0         | 14      |
| K- 07 35 06 85 | G 1/4 male   | Brown   | 47,0         | 17      |
| K- 07 35 06 86 | G 1/8 female | Brown   | 45,0         | 14      |
| K- 07 35 06 87 | G 1/4 female | Brown   | 47,0         | 17      |
| K- 07 35 06 88 | G 1/8 male   | mavi    | 45,0         | 14      |
| K- 07 35 06 89 | G 1/4 male   | mavi    | 47,0         | 17      |
| K- 07 35 06 90 | G 1/8 female | mavi    | 45,0         | 14      |
| K- 07 35 06 91 | G 1/4 female | mavi    | 47,0         | 17      |
| K- 07 35 06 92 | G 1/8 male   | kırmızı | 45,0         | 14      |
| K- 07 35 06 93 | G 1/4 male   | kırmızı | 47,0         | 17      |
| K- 07 35 06 94 | G 1/8 female | kırmızı | 45,0         | 14      |
| K- 07 35 06 95 | G 1/4 female | kırmızı | 47,0         | 17      |